

# DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS D350-607-2 REV. C AND  
INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D350-607 REV. 4

REF TCCA STC: SH94-14

REF FAA STC: SR00213NY

REF EASA STC: EASA.10016996

REF. ANAC STC: 2007S03-03/-04/-05/-06

## PURPOSE:

The purpose of this service instruction is to correct a typographical and pictorial errors in Detail A of Figure 4 (Installation Instructions D350-607-2) and Detail AA of Figure 25-9 (Instructions for Continued Airworthiness ICA-D350-607) as shown below. Also, note that any references to the D3810-1 Spring Plunger in Sections 3.1/3.3/3.4 of D350-607-2 and Sections 25.7/25.9/25.10 of ICA-D350-607 should be replaced with D3801-1 Spring Plunger.

**IS:**  
D3801-1 SPRING  
PLUNGER  
REF

**WAS:**  
D3810-1 SPRING  
PLUNGER  
REF

**DETAIL A - FWD MOUNT (D350-607-2)**  
**DETAIL AA - FWD MOUNT (ICA-D350-607)**

**DETAIL A (D350-607-2)**  
**DETAIL AA (ICA-D350-607)**

**FIGURE 4: FWD MOUNT (D350-607-2)**  
**FIGURE 25-9: FWD MOUNT (ICA-D350-607)**






(BASKET MESH NOT SHOWN FOR CLARITY)  
BASKET MAY BE INSTALLED ON EITHER LH OR RH SIDE.  
LH INSTALLATION ON HIGH GEAR SHOWN.  
LOW GEAR SIMILAR, D350-591 STEP MUST BE REMOVED.

CANADA  
DEPARTMENT OF TRANSPORT  
AIRCRAFT CERTIFICATION  
BRANCH  
DAO # 01-O-01

APPROVED

BY: *[Signature]*  
D. SHEPHERD (DE # 02)

DATE: 12.05.04  
CERT. NO.: SH94-14  
ISSUE NO.: 5

A	NEW ISSUE	(PAR12-181)	MB	12.05.02
REV.	DESCRIPTION		BY	DATE
DESIGN		<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA		
DRAWN				
CHECKED		DRAWING NO.	REV. A	
MFG. APPR.	N/A	DSI 9610	SHEET 1 OF 1	
APPROVED		TITLE	SCALE	
DE APPR.		PART NUMBER CORRECTION	NTS	
DATE	12.05.02	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		